




DISCOVER MORE OF OUR PRODUCTS HERE→



VIEW CATALOG

VINEYARD INCORPORATORS

FOR YEAR ROUND VINEYARD FLOOR MAINTENANCE

**PROTECT YOUR SOIL
AND ELEVATE YOUR
VINEYARD.**



The all-in-one implement that tills, weeds, levels, incorporates pruning chips, reduces compaction, and lightly firms the soil. Tractors make many passes in the vineyard throughout the year with even heavier equipment, which can cause deeper ruts and compaction. Our S Series Vineyard Incorporators leave the soil in a smooth and level condition which improves appearance and helps prevent future floor damage.



Uneven, compacted,
weedy vineyard rows



Tills, levels and rolls
out the vineyard floor



VINEYARD INCORPORATORS

TILLER FEATURES

- Cat. II, 3-point hitch
- 4 speeds @ 540 R.P.M. & 120 horsepower gearbox
- Strong, smooth running, all gear final drive
- Slip clutch driveshaft to protect tractor and tiller drive systems
- New super alloy tungsten carbide coated tines, with normal life 3 to 4 times longer over standard heat treated tines
- 6 tines mounted on each rotor plate for maximum tilling action
- Tines staggered in scroll design for easy soil penetration
- Gearbox supported by full length tubes for added support
- Torque tube frame to absorb shock loads
- Large, oil bath, long wearing rotor bearing
- Side mounted skids for depth control




4 speed gearbox



Tungsten coated tines

REAR ROLLER FEATURES

- 16" diameter x 1/4" wall steel tubing roller with adjustable mud scraper
- Turnbuckle height adjustment to obtain exact compaction required
- Easy to bolt up to standard S tiller
- Roller is 6" wider than side plates to eliminate ridges
- 2" diameter solid roller bearing shaft
- 1/2" plates between tiller and tailboard to contain the soil
- 4 tailboard turnbuckles to hold the tailboard in place for releasing the exact amount of soil to the roller
- Heavy 1"x 3" roller mounting brackets



Adjustable rear roller

SPECIFICATIONS

Model #	Tilling Width	Overall Width	No. of Tines	Max. H.P.	Weight
S160RR-CT	5' - 3" (63")	5' - 9" (69")	36	120	1,900 lbs.
S180RR-CT	6' - 1" (73")	6' - 6" (78")	42	120	2,090 lbs.



FORM #SI0020-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com