




DISCOVER MORE OF OUR PRODUCTS HERE→



TANDEM DISCS

"T" SERIES

BUILT TO LAST, DESIGNED TO PERFORM.

These heavy duty 3-point hitch tandem discs are excellent for leveling, pulverizing and thoroughly finishing seedbeds. The discs are also great for knocking down weeds. The strong rectangular tube frame is engineered for extra strength. Two main cross beams give the additional strength. The $\frac{3}{16}$ " x 22" blades are notched on the front gangs for better cutting, the rear gangs are smooth to give a leveling finish. The bearings are self aligning and factory lubricated for life. Bearings are square bore to keep blades from turning between spools.

CAT I & II
A. S. A. E.
QUICK
HITCH
COMPATIBLE



8 1/2" shown




TANDEM DISCS

FEATURES

- Category I & II, 3-point hitch
- 3/8" X 22" notched front and plain rear blades
- 1 1/8" high carbon square axles
- 7 1/2" long cast spool spacers
- Self aligning, triple sealed bearings
- 2" X 4" X 3/8" main frame and gang beams
- Easy gang adjustment with special pull handles
- Front and rear gangs adjustable to 7, 14 or 21 degrees



Cat. I & II clevis hitch



Double cross beams



Triple sealed bearings

SPECIFICATIONS

Model #	Cutting Width	Blade Diameter	No. of Blades	Weight
T1622	5' - 6"	22"	16	1,100 lbs.
T2022	6' - 6"	22"	20	1,230 lbs.
T2422	7' - 6"	22"	24	1,515 lbs.
T2822	8' - 6"	22"	28	1,660 lbs.



FORM #VA0003-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com