




Built By:

BWImplement

DISCOVER MORE OF OUR PRODUCTS HERE→



VIEW CATALOG

TANDEM DISCS


"VWT" SERIES - PULL TYPE

**TACKLE TOUGH SOIL
WITH OUR MEDIUM
DUTY TANDEM DISCS.**



FEATURES

- 4" x 4" x ¼" wall tubing main frame
- Easy pull pin adjustment on front and rear blade gangs
- 1 ½" square solid steel axles
- Greaseable trunnion mounted, triple sealed bearings with wear guards
- 24" diameter x 4.5 mm notched front and plain rear blades
- 9" steel spacer spools
- 6 bolt hub and spindle assy. with 2 - 9.5L x 15" 8-ply tires
- Wheel axles pivot on replaceable nylon bearings
- 3 ½" x 8 cylinder with depth control
- 1" x 3" center shank with adjustable foot piece, less sweep



1 ½" triple sealed bearing in cast trunnion mount housing



Self-leveling, spring cushioned hitch with hand crank

OPTIONS

- Adjustable blade scrapers
- Pair of dirt shields
- Rear hitch

SPECIFICATIONS

Model #	No. of Blades	Cutting Width	Weight
VWT24-16	16	5' - 8" to 7' - 0"	2,480 lbs.
VWT24-18	18	7' - 2" to 8' - 6"	2,600 lbs.
VWT24-20	20	7' - 2" to 8' - 6"	2,680 lbs.



FORM #BW0006-25

13477 Benson Ave. Chino, CA 91710 | 909/548-4848 | sales@gearmore.com