

IMPLEMENTS

FOR STAND-ON TRACK COMPACT LOADERS W/MINI CII MOUNT

COMPACT MOUNT



4 IN 1 BUCKETS



42" and 48" widths models available. Functions as a loader bucket, clam, grapple, dozer, box scraper, and bottom dump bucket. Has strong hinges and pins to distribute load.

Specifications 2008270 233333 Width (overall) 42" 48" Height (overall) 19.7" 19.7" Length 27.7" 27.7" Clam Opening 18.2" 18.2" Weight (lbs) 250# 281# *38" special order

	OIL	B / /		
RO	CK	RH	II.K	FTS.



Designed to collect rocks and debris, allowing soil to sift through. Rake design allows for fast cleanup, ground leveling and gathering materials away from buildings and obstructions. Leave the dirt and pay less at the land fill!

Specifications	19500
Width (overall)	42"
Height (overall)	15"
Length (overall)	25"
Tine Spacing (between tines)	2"
Tine Rod Diameter	1.13"
Weight (lbs)	184#

BRUSH GRAPPLES



Aggressive grapple made of high strength steel for maximum performance and durability. Cylinder guard design protects cylinder while preventing build-up of debris. Great for cleaning up and transporting branches, brush, and limbs.

Specifications	235962	235965
Width (overall)	42"	48"
Height (overall)	26"	26"
Length (overall)	31"	31"
Grapple Opening	29"	29"
Weight (lbs)	256#	275#

ROOT GRAPPLES



The aggressive tine shanks root
out objects below ground level.
The wide grapple opening allows
for gathering a large amount of
brush and debris. The hydraulically
operated grapple locks the
material in place and stabilizes it
for transport.

Specifications	124429	235928
Width (overall)	42"	48"
Height (overall)	28.4"	28.4"
Length(overall)	26.8"	26.8"
Tine Spacing	8.5"	8.5"
Grapple Opening	32"	32"
Weight (lbs)	268#	276#

ΔΙ	\mathbf{I}	- $-$		V/-	•
ΔII	uci	FR	RI	v =	_



The X15	500 hydr	aulic dig	ger is	the
most tr	ouble fr	ee digg	er on	the
market.	The unit	features	s an in	line
sealed	planetar	y gear	reduc	tior
drive de	sign. Th	is clean	, effec	tive
	ensures			
	Digger			
mount.	00 -			

Specifications	X1500
Min. Hyd. Flow	8 G.P.M.
Max. Hyd. Flow	16 G.P.M.
Max. Auger Diameter	30"
Output Shaft	2" Hex
Auger Diameters	6" - 30"

DA	11		$\hat{}$	п	v c
PA	ᄔ	EI		к	$\Lambda >$



High strength lightweight frame for large 2300 pound pay loads. Open guard for excellent visibility. Patented load retention ring. Available in tine length of 42" & 48".

	12331/	12331/
Specifications	106220	106222
Frame Width	40"	40"
Frame Height	31"	31"
Fork Thickness	1"	1"
Fork Width	3"	3"
Fork Length	42"	48"
Wt. Frame & Forks	210#	225#

Other implements and sizes are available on request.

