SWEEPSTER

RHFA Sweeper

PALADIN LIGHT CONSTRUCTION
BRADCO
FFC
HARLEY
McMILLEN
SWEEPSTER
The Power of Combined Excellence

For Category I or II 3 point hitch tractors

FEATURES:

- 5', 6', 7', or 8' widths available
- Rear mounted, mechanical drive sweeper sweeps forward or backward
- Designed for grounds maintenance and construction applications
- 30° manual angling standard hydraulic angling optional
- 5 to 8ft by 32" diameter brushes
- Optional sprinkler systems
- Storage stands standard
- Attaches to Category I or II 3 point hitches on the front or rear of tractors
- T-shaft gear box turns over to change brush rotation from forward to backward

RHFA Sweepers

STANDARD FEATURES:

Brush Drive
- Brush powered by 540 RPM PTO
- Power transmitted from gearbox to brush by telescoping constant velocity drive shaft

Mounting
- Mounts to ASAE Category I or II 3 point hitch on the front or rear
- Category I pins included and Category II pins are available

Brush
- 6ft (1.8m) by 32” (81.3cm) diameter sectional brush
- Choice of bristle material poly, wire, or poly/wire sets
- Designed for 10” (25.4cm) I.D. water type brush segments
- Detachable brush hood covers 120° of brush and ends

Brush Controls
- Manual angle change 30° to left & right
- Brush speed controlled by vehicle’s engine
- Plate swing standard
- Pressure adjusted by changing position of spring/chains
- Lift sweeper by raising tractor arms

Storage Stands
- Four permanent stands protect brush during storage

OPTIONAL FEATURES:

Brush Widths
- 5’, 7’, or 8’ widths available

Hydraulic Angle Change
- Hydraulic cylinder angles sweeper 30° left and right
- Cylinder, hoses and mounting brackets included
- Activating valve not included

180° Brush Hood

Dirt Deflector
- For 120° or 180° brush hoods and rear mounting units, attaches under framework between tractor & sweeper

Sprinkler System
- Spray nozzles mount to hood and supplies a fine curtain of water across face of brush reducing dust
- Includes electric pump, hoses, and spray nozzles
- 25 gallon (95 L) water tank available for customer to install

Specifications	
Width Standard 6 ft brush	72”
Sweeping Path	64”
Weight (lbs)	850

Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.

PH: (800) 456-7100

www.paladinbrands.com

PALADIN LIGHT CONSTRUCTION
BRADCO
FFC
HARLEY
McMILLEN
SWEEPSTER
The Power of Combined Excellence