



Stump Grinder

SmoothCut™ PTO Powered Stump Grinders

Economical and Efficient PTO powered stump grinders make stump removal fast and easy. Operator easily controls the stump grinder from the comfort of the tractor seat.



Features

- Maneuverable - goes anywhere a tractor can; gets into tight places.
- Increased productivity via it's unique cutting wheel design.
- Cutting wheel design provides a smoother cutting action.
- Easy to operate - hydraulic controls allow easy operation from the tractor seat using existing tractor hydraulic controls.
- Durable carbide-tipped cutting teeth are economical and easy to replace.
- Harden bushings used in major pivot points for increased reliability.
- Grease zerks provided at major pivot points for extended service life.
- SureFoot stabilizer bar provides secure footing during operation.
- Rubber deflector helps control chips and debris during grinding.
- Parking stand for easy storage.
- Two pair of remote hydraulic outlets are required on the tractor to operate the stump grinder.
- SG-26 designed for tractors 22 -50 PTO HP; SG-36 designed for tractors 45-100 PTO HP.
- Standard pressure relief valve for even control of cutting feed rate.

Stump Grinder Specifications		
	SG-26A	SG-36A
Hitch	Cat. I	Cat. I/II
Overall Estimated Length (in/cm)	75 / 191	80 / 230
Drive System Protection	Slip Clutch	Slip Clutch
Gearbox Rating/Ratio	60 HP / 1:1.5	100 HP / 1:1.46
Cutting Wheel Construction	Welded 2-piece Laminated Steel	
Cutting Wheel Thickness (in/cm)	3/4 / 1.91	7/8 / 2.22
Cutting Wheel Diameter (in/cm)	26 / 66	36 / 91
Cutting Wheel Speed	810 RPM	788 RPM
@ 540 PTO RPM	5,515 ft. / min.	7,430 ft. / min.
Number of Teeth	33	42
Cutting Teeth Construction	Carbide Steel Bolt-In	
Cut Height Above Ground (in/cm)	18 / 46	18 / 46
Cut Depth Below Ground (in/cm)	10 / 25	15 / 38
Maximum Horizontal Cut (in/cm)	28 / 71	33 / 84
Swing Arc	45°	45°
Minimum Power / Flow Required	22-PTO HP	45-PTO HP
Maximum Power / Flow	50-PTO HP	100-PTO HP
Driveline	PTO / Series 5	PTO / Series 6
PTO Speed	540 RPM	540 RPM
Weight (lbs/kg)	660 / 299	880 / 399
Product No.	812200	812210
Parts List	SG-26 Part List	SG-36 Part List
<i>* Be Sure front of tractor is properly counterbalanced with front-end weights or front-end loader.</i>		

- 
 Read and understand Operator's Manual before operation.
- 
 Stump Grinder will put a heavy load on the rear of your tractor. Be sure front of tractor is properly counterbalanced with weights.
- 
 Never allow children or bystanders around tractor or stump grinder when you are using equipment.

WORKSAVER, INC.
 P.O. BOX 100
 9 Worksaver Trail
 Litchfield, Illinois 62056-0100 USA
 Phone: (217) 324-5973
 Fax: (217) 324-3356

