



 ΔM

Model 300 Digger for Sub-compact Tractors



Model 720 Heavy Duty Digger



Model 500Standard Duty Digger



Model 925Industrial Digger



DIG DEEPER, FASTER & SMARTER

The Worksaver Post Hole Diggers are engineered to allow the operator to dig deeper, faster and smarter. Worksaver's line of PTO powered diggers offer time saving convenience with outstanding reliability. Shear bolt protected driveline is coupled to a rugged gearbox featuring tapered roller bearings and spring loaded seals for extended service life. Large 2" output shaft has two bolt auger connection for reliable power transfer. All job matched augers utilize fishtail center points with double flighting on the first turn for quick, positive digging action right from the start.

Marketed by:



Worksaver

Worksaver Post Hole Diggers Dig Deeper, Faster & Smarter

<u>Model 300</u> is ideal for the small acreage owners. This model mates to most sub-compact tractors with a Cat. 0 or limited Cat. I, 3-point hitch. Standard positioning handle allows the operator to position the auger from the tractor seat. Augers 30" in length are offered in 6", 9" and 12" diameters providing versatility when digging holes.

Model 500 is the most popular digger. This standard duty digger offers 3 position boom adjustment allowing it to adapt to most tractors. Tubular steel stock of 2.875" diameter is used for the boom for increased durability. Horse-shoe yoke allows the unit to operate on Cat. I tractors offering the operator versatility of use. Job matching augers is easy; they are 42" in length in 6", 9" and 12" diameters in double flight configuration. Position handle is standard equipment.

Model 720 offers increased performance on this heavy duty digger. Designed for Cat. I/II tractors, this model offers 3 position boom adjustment, rugged gearbox along with 3 1/2" diameter boom for dependable operation. Augers (42" length) are available in 6", 9", 12", 14", 18" and 24" diameters in double flight and heavy duty configuration offering the outmost in productivity.

<u>Model 925</u> industrial duty workhorse provides dependable operation when mated with any auger from 6" to 30" in diameter. It fits any Cat. I/II tractor with 540 rpm PTO. When maximum performance is required, the 4.1:1 ratio gearbox provides the torque to make the operator more productive.

Model (Code No.):	300 (170545)	500 (170990)	720 (706160)	925 (709540)
Boom Size (O.D.)	2.875"	2.875"	3.5"	3.5"
Yoke Size	1/2" x 3" HRF	3"	3"	3"
Boom Positions	3	3	3	3
Mount Type	Cat. 0 (7/8" Pins)	Cat. I	Cat. I	Cat. I
Gearbox Ratio	3:1	3:1	3.18:1	4.1:1
Gearbox Output Shaft	2"	2"	2"	2"
Gearbox Bearings	Tapered Roller	Tapered Roller	Tapered Roller	Tapered Roller
Gearbox Seals	Double lip, spring loader			
Drive Type	PTO, 540 RPM	PTO, 540 RPM	PTO, 540 RPM	PTO, 540 RPM
Shear Bolt	Yes, Grade 2	Yes, Grade 2	Yes, Grade 2	Yes, Grade 2
Gearbox Ltd. Warranty	5 Years	5 Years	5 Years	5 Years
Tractor HP	Up to 25 HP	20 - 35 HP	25 - 65 HP	40 - 95 HP
Optional Down Force Kit	N/A	Yes, DFK-50	Yes, DFK-70	Yes, DFK-90
Auger Sizes	6" thru 12"	6" thru 12"	6" thru 24"	6" thru 30"
Auger Length	30"	42"	42"	42"
Auger Type	STD*	HDDF*	HDDF*	HDDF*
Auger Point - Bolt-in	Fishtail	Fishtail	Fishtail	Fishtail
12" Auger Ext.	N/A	Opt. (170705)	Opt. (170705)	Opt. (170705)
Parking Stand Kit	Opt. (102160)	Opt. (102165)	Opt. (102165)	Opt. (102170)
Weight (lbs.)	149#	160#	206#	220#

^{*}STD - standard duty augers for use in lighter soils, free of stones, roots etc.

13477 Benson Ave. Chino, CA 91710 Ph: 909/548-4848 sales@gearmore.com

^{*}HDDF - Heavy duty double flight augers for use when encountering tougher digging conditions or where stones, roots, etc. may be present, designed to help carry soil to the surface of the hole